

Technical sheet :

4 IN 1 BUCKET WITH TEETH



Technical characteristics

- 4 in 1 bucket suitable for handling materials with a density ≤ 2100 kg/m³ (131 lb/ft³).
- Rear bolted counter blade dedicated to levelling.
- Claws fitted on the mobile part's back side help handling cylindrical objects such as poles, tubes etc.
- Reinforced structure (base, blade and sides).

[The 3D picture at the top of this page is the reference B4x1 340/1500 - 52707200].

Customer benefits

- Versatile and very robust bucket.
- Designed for executing different operations :
 - Loading and unloading operations
 - Leveling ground
 - Backfilling trenches
 - Clamping and grabbing

		B4X1 1500/340 4P	B4X1 1500/340 EU	CB4X1 1500/340 SK	CB4X1 400/1500	CB4x1 400/1500 SK	CB4x1 700/1950	CB4x1 850/2300	CB4x1 900/2450
Reference number		52742064	52742065	52707200	52551750	52000785	751402	751401	751465
Heaped capacity (US gal)		89	89	89	106	106	185	224	237
Struck capacity (US gal)		69	69	69	83	83	138	166	178
Overall weight (lb)		752	745	761	1179	1102	1340	1504	1574
Height (in)		2' 10"	2' 10"	2' 10"	2' 11"	2' 11"	2' 11"	2' 11"	2' 11"
Length (in)		3' 2"	3' 2"	3' 2"	3' 8"	3' 6"	3' 8"	3' 8"	3' 8"
Width (in)		5'	5'	5'	5'	5'	6' 5"	7' 7"	8'
Depth (in)	p5	2' 7"	2' 7"	2' 3"	3' 3"	2' 7"	2' 11"	3' 8"	2' 11"
Required machine equipment									
Bucket type		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Tooth type		Forged	Forged	Forged	Forged	Forged	Forged	Forged	Forged
Tooth connection		Pin on	Pin on	Pin on	Pin on	Pin on	Pin on	Pin on	Pin on
Cutting edge		No	No	No	No	No	No	No	No
Number of tooth		4	4	4	4	4	5	6	7
E-RECO		No	No	No	No	No	No	No	No
Connection system		4-point	Euro	Universal Quick-attach	Manitou	Universal Quick-attach	Manitou	Manitou	Manitou

Machines compatibility								
GCT 3-14	X	X	X	-	-	-	-	-
GCT 3-14+	X	X	X	-	-	-	-	-
MLT 420-60 H	-	-	-	X	-	-	-	-
MLT 625-75 H	-	-	-	-	-	X	-	-
MLT 625 e	-	-	-	-	-	X	-	-
MLT 635-130 PS+ (S1)	-	-	-	-	-	-	-	X
MLT 635-130 PS+ (S2)	-	-	-	-	-	-	-	X
MLT 635-140 V+ (S1)	-	-	-	-	-	-	-	X
MLT 635-140 V+ (S2)	-	-	-	-	-	-	-	X
MLT 733-115	-	-	-	-	-	-	-	X
MLT 733-115 (S2)	-	-	-	-	-	-	-	X
MLT 733-115 LSU (S1)	-	-	-	-	-	-	-	X
MLT 737-130 PS+ (S1)	-	-	-	-	-	-	-	X
MLT 738-130 PS+ (S1)	-	-	-	-	-	-	-	X
MLT 741-130 PS+ (S1)	-	-	-	-	-	-	-	X
MLT 741-140 V+ (S1)	-	-	-	-	-	-	-	X
MLT 742-130 PS+ (S1)	-	-	-	-	-	-	-	X
MLT 742-140 V+ (S1)	-	-	-	-	-	-	-	X
MLT 841-145 PS+	-	-	-	-	-	-	-	X
MLT 850-145 V+	-	-	-	-	-	-	-	X
MLT 940-140 V+ (S1)	-	-	-	-	-	-	-	X
MLT 940-140 V+ (S2)	-	-	-	-	-	-	-	X
MLT-X 625-75 H	-	-	-	-	-	X	-	-
MLT-X 732	-	-	-	-	-	-	-	X
MLT-X 735 T LSU	-	-	-	-	-	-	-	X
MLT-X 738-130 PS+ (S1)	-	-	-	-	-	-	-	X
MLT-X 841 - 145 PS+	-	-	-	-	-	-	-	X
MLT-X 850-145 V+	-	-	-	-	-	-	-	X
MLT-X 1035 LT LSU	-	-	-	-	-	X	X	X
MT 420 H	-	-	-	X	-	-	-	-
MT 420 H SKID	-	-	-	-	X	-	-	-
MT 625 e	-	-	-	-	-	X	-	-
MT 625 H	-	-	-	-	-	X	-	-
MT 625 H Comfort	-	-	-	-	-	X	-	-
MT 730 H	-	-	-	-	-	X	-	-
MT 735 75D ST5	-	-	-	-	-	-	X	X
MT 930 H	-	-	-	-	-	X	-	-
MT 935 75D ST5	-	-	-	-	-	-	X	X
MT 1135 75 D	-	-	-	-	-	-	X	X
MT 1135 H 100D	-	-	-	-	-	-	X	X
MT 1335 75D ST5	-	-	-	-	-	-	X	X
MT 1335 100D ST5	-	-	-	-	-	-	X	X
MT 1335 H 75D ST5	-	-	-	-	-	-	X	X
MT 1335 H 100D ST5	-	-	-	-	-	-	X	X
MT 1335 HA 75D ST5	-	-	-	-	-	-	X	X
MT 1335 HA 100D ST5	-	-	-	-	-	-	X	X
MT 1440	-	-	-	-	-	-	X	X
MT 1440 e	-	-	-	-	-	-	X	X
MT 1440 easy ST5	-	-	-	-	-	-	X	X
MT 1440 ST5	-	-	-	-	-	-	X	X
MT 1840	-	-	-	-	-	-	X	X
MT 1840 e	-	-	-	-	-	-	X	X
MT 1840 easy ST5	-	-	-	-	-	-	X	X
MT 1840 ST5	-	-	-	-	-	-	X	X
MT-X 420 H	-	-	-	X	-	-	-	-
MT-X 625 H	-	-	-	-	-	X	-	-
MT-X 625 H Comfort	-	-	-	-	-	X	-	-
MT-X 625 HA Comfort	-	-	-	-	-	X	-	-
MT-X 735	-	-	-	-	-	-	X	X
MT-X 1135	-	-	-	-	-	-	X	X

	B4X1 1500/340 4P	B4X1 1500/340 EU	CB4X1 1500/340 SK	CB4X1 400/1500	CB4x1 400/1500 SK	CB4x1 700/1950	CB4x1 850/2300	CB4x1 900/2450
MT-X 1440	-	-	-	-	-	-	X	X
MT-X 1840	-	-	-	-	-	-	X	X
MXT 840 P	-	-	-	-	-	-	-	X
MXT 840 P IND	-	-	-	-	-	-	-	X
MXT 1740 P	-	-	-	-	-	-	-	X
RS 4-14	-	-	-	X	-	-	-	-
TX 408	-	-	-	-	-	-	-	X
TX 4017	-	-	-	-	-	-	-	X
ULM 412 H	X	X	X	-	-	-	-	-
ULM 415 H	X	X	X	-	-	-	-	-
MLT 635-130 PS+ ST4 OLD	-	-	-	-	-	-	-	X
MLT 635-140 V+ ST4 OLD	-	-	-	-	-	-	-	X
MLT 733-115 LSU ST4 OLD	-	-	-	-	-	-	-	X
MLT 733-115 ST4 OLD	-	-	-	-	-	-	-	X
MLT 737-130 PS+ ST4 OLD	-	-	-	-	-	-	-	X
MLT 741-140 V+ ST4 OLD	-	-	-	-	-	-	-	X
MLT 840-145 PS+ OLD	-	-	-	-	-	-	-	X
MLT 845-100 H OLD	-	-	-	-	-	X	X	X
MLT 845-120 OLD	-	-	-	-	-	X	X	X
MLT 940-140 V+ ST4 OLD	-	-	-	-	-	-	-	X
MLT 1040-145 PS+ L OLD	-	-	-	-	-	-	-	X
MLT-X 737-130 PS+ OLD	-	-	-	-	-	-	-	X
MLT-X 737-130 PS+ (S2) OLD	-	-	-	-	-	-	-	X
MLT-X 741-140 V+ OLD	-	-	-	-	-	-	-	X
MLT-X 741-140 V+ S1 OLD	-	-	-	-	-	-	-	X
MLT-X 840-140 PS+ OLD	-	-	-	-	-	-	-	X
MLT-X 845-120 OLD	-	-	-	-	-	X	X	X
MLT-X 845-120 H OLD	-	-	-	-	-	X	X	X
MLT-X 1040-140 PS+ L OLD	-	-	-	-	-	-	-	X
MT 625 HA OLD	-	-	-	-	-	X	-	-
MT 733 Easy OLD	-	-	-	-	-	-	-	X
MT 930 HA OLD	-	-	-	-	-	X	-	-
MT 933 Easy OLD	-	-	-	-	-	-	-	X
MT 1033 easy OLD	-	-	-	-	-	X	X	X
MT 1135 easy ST5 OLD	-	-	-	-	-	-	-	X
MT 1135 H easy ST5 OLD	-	-	-	-	-	-	-	X
MT 1135 HA Easy ST5 OLD	-	-	-	-	-	-	-	X
MT 1135 ST5 OLD	-	-	-	-	-	-	-	X
MT 1335 OLD	-	-	-	-	-	-	-	X
MT 1335 easy ST5 OLD	-	-	-	-	-	-	-	X
MT 1335 H easy ST5 OLD	-	-	-	-	-	-	-	X
MT 1335 HA easy ST5 OLD	-	-	-	-	-	-	-	X
MT 1335 ST5 OLD	-	-	-	-	-	-	-	X
MT 1440 A ST4 OLD	-	-	-	-	-	X	X	X
MT 1440 A ST5 OLD	-	-	-	-	-	-	X	X
MT 1440 HA ST4 OLD	-	-	-	-	-	X	X	X
MT 1440 HA ST5 OLD	-	-	-	-	-	-	X	X
MT 1840 A ST5 S1 OLD	-	-	-	-	-	-	X	X
MT 1840 A STG4 OLD	-	-	-	-	-	X	X	X
MT 1840 HA ST4 OLD	-	-	-	-	-	X	X	X
MT 1840 HA ST5 S1 OLD	-	-	-	-	-	-	X	X
MT-X 733 OLD	-	-	-	-	-	X	X	X
MT-X 733 Mining OLD	-	-	-	-	-	X	X	X
MT-X 1033 OLD	-	-	-	-	-	X	X	X
MT-X 1440 A OLD	-	-	-	-	-	-	X	X
MT-X 1840 A OLD	-	-	-	-	-	-	X	X

TABLE SYMBOL

	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes